

# VYBO Electric a.s.



## Data Sheet

No.

Three Phase Induction Motor

Drawing No.

Customer	
Client reference	
Type	1AL-71M 2-6 0,25KW 230/400V 50HZ
Brand	VYBO Electric

### Identification

Type:	1AL-71M 2-6	Frame:	71	mm
Power:	0,25 kW	Poles:	6	P
Rated Current:	380 V	A	Rated Voltage:	230 / 400 V
	400 V		Connection:	Δ/Y
	415 V		Insulation Class:	F
Speed:	870 rpm	Temperature Rise:		
Frequency:	50 Hz	Service Factor:	1,0	
Direct on line starting torque ratio (LRT/RLT):	2,0	Duty:	S1, S2, S3, S4-S9	
Direct on line pull out torque ratio (BDT/RLT):	1,9	Ambient Temperature:	-35 ~ 50°C (On request possible 62°C)	
Direct on line starting current ratio (LRA/RLA):	4,0	Altitude:	1000m	
Efficiency:	59 %	Protection Degree:	IP55	
Power factor:	0,68	Cooling:	IC411	
Noise level:	52 dB(A)	Mounting:	IM B (On request)	
Weight:	6,3 kg	Vibration:	2.8 mm/s	
Rotor inertia:	0,0014 kg/m2	Direction of Rotation:	Both	
		Starting Method:	DOL or VFD	
		Coupling:	DIRECT	
		Load Type:	Parabolic or linear curve	
		Terminal box:	2-M20X1.5	



### Bearing Information

	DE	NDE
Bearing:	62022Z	62022Z
Regreasing int.(h):		
Grease amount(g):		
Grease:		

### Notes / Accessories

### Deviation Sheet

	VYBO Electric		Customer

### Standards

Specification:	IEC60034-1 / GB755
Test:	IEC60034-2 / GB/T1032
Noise:	IEC60034-9 / GB10069.3
Vibration:	IEC60034-14 / GB10068

### Edition

Performed	Checked	Date

Item	Changes	Performed	Checked	Date