

VYBO Electric a.s.



Data Sheet

No.

Three Phase Induction Motor

Drawing No.

Customer	
Client reference	
Type	1AL-112M-6 2,2KW 230/400V 50HZ
Brand	VYBO Electric

Identification

Type:	1AL-112M-6		Frame:	112	mm		
Power:	2,2	kW	Poles:	6	P		
Rated Current:	380 V	5,6	Rated Voltage:	230	/	400	V
	400 V	5,32		Connection:	Δ/Y		
	415 V	5,1			Insulation Class:	F	
Speed:	935	rpm	Temperature Rise:				
Frequency:	50	Hz	Service Factor:	1,0			
Direct on line starting torque ratio (LRT/RLT):	2,1		Duty:	S1, S2, S3, S4-S9			
Direct on line pull out torque ratio (BDT/RLT):	2,0		Ambient Temperature:	-35 ~ 50°C (On request possible 62°C)			
Direct on line starting current ratio (LRA/RLA):	6,5		Altitude:	1000m			
Efficiency:	79	%	Protection Degree:	IP55			
Power factor:	0,76		Cooling:	IC411			
Noise level:	65	dB(A)	Mounting:	IM B (On request)			
Weight:	28	kg	Vibration:	2.8 mm/s			
Rotor inertia:	0,014	kg/m2	Direction of Rotation:	Both			
			Starting Method:	DOL or VFD			
			Coupling:	DIRECT			
			Load Type:	Parabolic or linear curve			
			Terminal box:	2-M32X1.5			



Bearing Information

	DE	NDE
Bearing:	63062Z	63062Z
Regreasing int.(h):		
Grease amount(g):		
Grease:		

Notes / Accessories

Deviation Sheet

	VYBO Electric	Customer

Standards

Specification:	IEC60034-1 / GB755
Test:	IEC60034-2 / GB/T1032
Noise:	IEC60034-9 / GB10069.3
Vibration:	IEC60034-14 / GB10068

Edition

Performed	Checked	Date

Item	Changes	Performed	Checked	Date