

# VYBO Electric a.s.



## Data Sheet

No.


Three Phase Induction Motor

Drawing No.

Customer	
Client reference	
Type	1LCZ-355L-4 280KW 400/690V 50HZ
Brand	VYBO Electric

### Identification

Type:	1LCZ-355L-4	Frame:	355	mm
Power:	280 kW	Poles:	4	P
Speed:	1490 rpm	Rated Voltage:	400 / 690	V
Frequency:	50 Hz	Connection:	Δ/Y	
Rated Current:	400 V	478 A	Insulation Class:	
	690 V		F	
Efficiency:	IE1	94	Service Factor:	
	100%	95	1,0	
	75%	94,4	Duty:	
	50%	93,4	S1, S2, S3, S4-S9	
Power factor:	0,9	Ambient Temperature:	-35 ~ 50°C (On request possible 62°C)	
Noise level:	101 dB(A)	Altitude:	1000m	
Weight:	1719 kg	Protection Degree:	IP55	
		Cooling:	IC411	
		Mounting:	IM B (On request)	
		Vibration:	2.8 mm/s	
		Direction of Rotation:	Both	
		Starting Method:	DOL or VFD	
		Coupling:	DIRECT	
		Load Type:	Parabolic or linear curve	
		Terminal box:	2-M63X1.5	



### Bearing Information

	DE	NDE
Bearing:	NU322C3	6322C3
Regreasing int.(h):		
Grease amount(g):		
Grease:		

### Notes / Accessories

### Deviation Sheet

	VYBO Electric	Customer

### Standards

Specification:	IEC60034-1 / GB755
Test:	IEC60034-2 / GB/T1032
Noise:	IEC60034-9 / GB10069.3
Vibration:	IEC60034-14 / GB10068

### Edition

Performed	Checked	Date

Item	Changes	Performed	Checked	Date