

# VYBO Electric a.s.



## Data Sheet

No.

Three Phase Induction Motor

Drawing No.

Customer	
Client reference	
Type	4LC-200L 2-6 22KW 400/690V 50HZ
Brand	VYBO Electric

### Identification

Type:	4LC-200L 2-6		Frame:	200		mm
Power:	22	kW	Poles:	6		P
Rated Current:	380 V	44	Rated Voltage:	400	/	690 V
	400 V	41,8		Connection:	Δ/Y	
	415 V	40,3			Insulation Class:	F
Speed:	985	rpm	Temperature Rise:			
Frequency:	50	Hz	Service Factor:	1,0		
Direct on line starting torque ratio (LRT/RLT):	2		Duty:	S1, S2, S3, S4-S9		
Direct on line pull out torque ratio (BDT/RLT):	2,1		Ambient Temperature:	-35~50°C		
Direct on line starting current ratio (LRA/RLA):	8,5		Altitude:	1000m		
Efficiency:	93,7	%	Protection Degree:	IP55		
Power factor:	0,81		Cooling:	IC411		
Noise level:	74	dB(A)	Mounting:	IM B (On request)		
Weight:	288	kg	Vibration:	2.8 mm/s		
Rotor inertia:	0,42911	kg/m2	Direction of Rotation:	Both		
			Starting Method:	DOL or VFD		
			Coupling:	DIRECT		
			Load Type:	Parabolic or linear curve		
			Terminal box:	2-M50X1.5		



### Bearing Information

	DE	NDE
Bearing:	6312C3	6312C3
Regreasing int.(h):		
Grease amount(g):		
Grease:		

### Notes / Accessories

### Deviation Sheet

	VYBO Electric	Customer

### Standards

Specification:	IEC60034-1 / GB755
Test:	IEC60034-2 / GB/T1032
Noise:	IEC60034-9 / GB10069.3
Vibration:	IEC60034-14 / GB10068

### Edition

Performed	Checked	Date



Item	Changes	Performed	Checked	Date